technical threads

Coated U Bolt Spec Sheet





Standard configuration includes the following:

- Black Neoprene-Coated Low Carbon Steel Hot Dip Galvanized U Bolt
- ASTM A563 Heavy Hex Nuts (4 per bolt standard)
- White Delrin Eye-Rod

Options include:

- A194 2H Heavy Hex Nuts
- Teflon Coating on rod and nuts
- Neoprene Pad instead of rod
- Many more options are available

technical threads LLC

Standard Bolt Dimensions

Rod & Pipe Size	Dia.	Ins. Width	Ins. Length	Thd
4/4 :: 4/4	4/4"	0/4011	0.4/0!!	0.0/0"
1/4 x 1/4	1/4"	9/16"	3 1/8"	2 3/8"
1/4 x 3/8	1/4"	3/4"	3 5/16"	2 3/8"
1/4 x 1/2	1/4"	15/16"	3 5/16"	2 3/8"
1/4 x 3/4	1/4"	1 1/8"	3 7/16"	2 3/8"
1/4 x 1	1/4"	1 3/8"	3 1/2"	2 3/8"
3/8 x 3/4	3/8"	1 1/8"	3 7/16"	2 3/8"
3/8 x 1	3/8"	1 3/8"	3 9/16"	2 3/8"
3/8 x 1 1/4	3/8"	1 3/4"	3 3/4"	2 1/2"
3/8 x 1 1/2	3/8"	2"	4"	2 1/2"
3/8 x 2	3/8"	2 7/16"	4 9/16"	2 1/2"
1/2 x 2	1/2"	2 7/16"	4 5/8"	2 1/2"
1/2 x 2 1/2	1/2"	3"	5 3/16"	3"
1/2 x 3	1/2"	3 5/8"	5 3/4"	3"
1/2 x 3 1/2	1/2"	4"	6 3/8"	3"
1/2 x 4	1/2"	4 5/8"	6 3/4"	3"
1/2 x 5	1/2"	5 5/8"	8"	3"
5/8 x 6	5/8"	6 3/4"	9 7/16"	3 3/4"
5/8 x 8	5/8"	8 3/4"	11 7/16"	3 3/4"
3/4 x 10	3/4"	10 7/8"	13 3/4"	4"
7/8 x 12	7/8"	12 7/8"	16"	4 1/2"
7/8 x 14	7/8"	14 1/4"	17 1/4"	4 1/2"
7/8 x 16	7/8"	16 1/4"	19 1/4"	4 1/2"
1 x 18	1"	18 1/4"	21 5/8"	6"
1 x 20	1"	20 1/4"	24 5/8"	6"
1 x 22	1"	22 1/4"	25 5/8"	6"
1 x 24	1"	24 1/4"	27 5/8"	6"
1 x 30	1"	30 1/4"	35"	6"
1 x 36	1"	36 1/4"	40 1/4"	6"

Note: Smaller size delrin is 7/16" and larger size is 11/16".

technical threads LLC

The information presented is believed to be accurate at the time of document creation. However, Technical Threads LLC is not responsible for any claim traceable to any errors as contained herein. Technical Threads LLC makes no warranties as to the accuracy of this information.